FAR EAST GOLD LIMITED ACN 639 887 219 THIRD SUPPLEMENTARY PROSPECTUS

IMPORTANT INFORMATION

This is a third supplementary prospectus (**Third Supplementary Prospectus**) and is intended to be read with the second supplementary prospectus dated 20 January 2022 (**Second Supplementary Prospectus**), supplementary prospectus dated 22 December 2021 (**First Supplementary Prospectus**) and the replacement prospectus dated 1 December 2021 (**Replacement Prospectus**) issued by Far East Gold Limited (ACN 639 887 219) (**Company**).

This Third Supplementary Prospectus is dated 28 January 2022 and was lodged with the Australian Securities and Investments Commission (**ASIC**) on that date. ASIC, the ASX and their respective officers take no responsibility for the contents of this Third Supplementary Prospectus.

This Third Supplementary Prospectus should be read together with the Second Supplementary Prospectus, First Supplementary Prospectus and Replacement Prospectus. Other than as set out below, all details in relation to the First Supplementary Prospectus and Replacement Prospectus remain unchanged. Terms and abbreviations defined in the Second Supplementary Prospectus, First Supplementary Prospectus and Replacement Prospectus have the same meaning in this Third Supplementary Prospectus. If there is a conflict between the Second Supplementary Prospectus, First Supplementa

This Third Supplementary Prospectus will be issued with the Second Supplementary Prospectus, First Supplementary Prospectus and Replacement Prospectus in hard copy or as an electronic copy and may be accessed on the Company's website at https://www.fareast.gold/home

This is an important document and should be read in its entirety. If you do not understand it, youshould consult your professional advisers without delay.

The Directors believe that the changes in this Third Supplementary Prospectus are not materially adverse from the point of view of an investor.

1. WOYLA SAMPLES – JORC TABLE

The Company provides additional information in respect of the exploration results included in the Second Supplementary Prospectus at Annexure A.

2. COMPETENT PERSON STATEMENT

This information which relates to exploration results is based on information compiled by Far East Gold staff and contractors and approved by Michael C Corey, PGeo., who is a Member of the Professional Geoscientists of Ontario, Canada. Michael Corey is a consultant to the Company and has sufficient experience which is relevant to the style of mineralisation and type of deposits under consideration. The activity which he is undertaking to qualify as a Competent Person as defined in the 2012 Edition of the 'Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves'. Michael Corey has consented to the inclusion in this report of the matters based on his information in the form and context in which they appear.

3. DIRECTORS' AUTHORISATION

This Third Supplementary Prospectus is issued by the Company and its issue has been authorised by a resolution of the Directors.

In accordance with section 720 of the Corporations Act, each Director has consented to

the lodgement of this Third Supplementary Prospectus with ASIC.

1 Paul Walker

CHAIRMAN For and on behalf of FAR EAST GOLD LTD

Annexure A

ATTACHMENT X

JORC Code, 2012 Edition – Table 1 report SPL1454

Section 1 Sampling Techniques and Data

(Criteria in this section apply to all succeeding sections.)

Criteria	JORC Code explanation	Commentary
Sampling techniques	 Nature and quality of sampling (eg cut channels, random chips, or specific specialised industry standard measurement tools appropriate to the minerals under investigation, such as down hole gamma sondes, or handheld XRF instruments, etc). These examples should not be taken as limiting the broad meaning of sampling. Include reference to measures taken to ensure sample representivity and the appropriate calibration of any measurement tools or systems used. Aspects of the determination of mineralisation that are Material to the Public Report. In cases where 'industry standard' work has been done this would be relatively simple (eg 'reverse circulation drilling was used to obtain 1 m samples from which 3 kg was pulverised to produce a 30 g charge for fire assay'). In other cases more explanation may be required, such as where there is coarse gold that has inherent sampling problems. Unusual commodities or mineralisation. 	 Rock samples were collected from quartz veins exposed on surface and within hand dug artisanal miner pits. Individual samples were comprised as pieces of the vein(s) material chipped the exposure. Effort was made to chip across the vein perpendicular to vein trend. Samples were collected from zones of visible sulphide mineralization and or alteration such as clay-pyrite or manganese. Samples were bagged and tagged with unique numbered assay tags inserted into each sample. The samples were delivered via commercial carrier to Pt. Geoservices Geoassay Mineral Laboratory located in Cikarang, Bekasi, West Java, Indonesia. The samples were oven dried at 105°C, weighed then jaw crushed to 70% less than 2mm, riffle split to obtain 250g, that was then pulverized to >85% passing 75 microns. Two splits were taken from this product, one for analysis the other for QAQC. Each sample was analysed for gold using FAA30 fire assay method using a 30g charge with an AAS finish. Samples containing >50 g/t (ppm) Au were further assayed using the FAGRAV gravimetric method. Ag, base metals and a suite of other elements were estimated by method GA102-ICP, which used an aqua regia digest with ICP-OES finish. Samples containing >100ppm Ag were further assayed using GOA-02 method which was an aqua regia ore grade digest with an AA finish.
Drilling techniques	 Drill type (eg core, reverse circulation, open- hole hammer, rotary air blast, auger, Bangka, sonic, etc) and details (eg core diameter, triple or standard tube, depth of diamond tails, face- sampling bit or other type, whether core is oriented and if so, by what method, etc). 	•

Criteria	JORC Code explanation	Commentary
Drill sample recovery	 Method of recording and assessing core and chip sample recoveries and results assessed. 	•
	• Measures taken to maximise sample recovery and ensure representative nature of the samples.	
	• Whether a relationship exists between sample recovery and grade and whether sample bias may have occurred due to preferential loss/gain of fine/coarse material.	
Logging	• Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and metallurgical studies.	•
	 Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc) photography. 	
	• The total length and percentage of the relevant intersections logged.	
Sub-sampling techniques and sample preparation	 If core, whether cut or sawn and whether quarter, half or all core taken. If non-core, whether riffled, tube sampled, rotary split, etc and whether sampled wet or dry. For all sample types, the nature, quality and appropriateness of the sample preparation technique. Quality control procedures adopted for all subsampling stages to maximise representivity of samples. Measures taken to ensure that the sampling is representative of the in situ material collected, including for instance results for field 	 The analytical methods selected are deemed appropriate for the level of analytical accuracy required at this early stage of exploration. The objective of the sampling was to determine where significant Au-Ag mineralization resides within the various textural types of quartz veins and alteration types that occur. The sample preparation completed at Pt.Geoservices prior to analysis are deemed appropriate for surface rock samples. Select high grade Au samples will also be analysed using a screen fire assay technique to determine if any coarse Au (+200 mesh) occurs.
	 duplicate/second-half sampling. Whether sample sizes are appropriate to the grain size of the material being sampled. 	

Criteria	JORC Code explanation	Commentary
Quality of assay data and laboratory tests	 The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total. For geophysical tools, spectrometers, handheld XRF instruments, etc, the parameters used in determining the analysis including instrument make and model, reading times, calibrations factors applied and their derivation, etc. Nature of quality control procedures adopted (eg standards, blanks, duplicates, external laboratory checks) and whether acceptable levels of accuracy (ie lack of bias) and precision have been established. 	 Assaying was completed by Pt. Geoservices Geoassay Mineral Laboratory in Cikarang, West Java, Indonesia. Pt. Geoservices is accredited for chemical testing under The laboratory maintains certification to ISO17025, ISO9001 and ISO 45001 standards. Pt. Geoservices conducts routine internal quality control, and review of this data suggests there are no issues with either precision or accuracy. FEG maintains a QAQC protocol for field samples whereby a single certified reference material (CRM) and a sample blank with unique assay number tags are included in each batch of 50 samples.
Verification of sampling and assaying	 The verification of significant intersections by either independent or alternative company personnel. The use of twinned holes. Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols. Discuss any adjustment to assay data. 	 Collected sample locations, descriptions and photographs, assay and QAQC data and protocols were reviewed by the company Qualified Person, Michael Corey P.Geo. All field and laboratory data is entered into an Excel database with QA/QC templates included. No adjustments to the assay data has occurred.
Location of data points	 Accuracy and quality of surveys used to locate drill holes (collar and down-hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation. Specification of the grid system used. Quality and adequacy of topographic control. 	• Samples site locations were determined with hand held GPS devices giving less than 5m accuracy. The mapping grid is WGS 84, UTM Zone 47 North. Topographic reference is provided by permanent monuments established by previous exploration in 1996.
Data spacing and distribution	 Data spacing for reporting of Exploration Results. Whether the data spacing and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied. Whether sample compositing has been applied. 	 Sample locations were selected based on vein exposures. No attention was given to collecting samples at a predetermined spacing. No JORC compliant mineral resources has been estimated for the Woyla project area. No sample compositing has been applied.
Orientation of data in relation to geological structure	 Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is known, considering the deposit type. If the relationship between the drilling orientation and the orientation of key mineralised structures is considered to have introduced a sampling bias, this should be assessed and reported if material. 	 Samples were collected to obtain some information of Au-Ag grade distribution within the textural types of quartz veins and alteration that occur within the Woyla project area. Samples comprise material chipped using rock hammer from across the exposed quartz vein. Effort was made to ensure samples were collected perpendicular to the vein and controlling structural trends.

Criteria	JORC Code explanation	Commentary
Sample security	• The measures taken to ensure sample security.	 Sample batches were packed into sealed and annotated rice sacks and transported by the company via commercial transport to the Pt Geoservices laboratory in Cikarang. Pt. Geoservices sample submission forms were cross-checked with Sample Receipt Confirmation notes issued by the Laboratory. Laboratory results were emailed to the Exploration Manager and Qualified Person.
Audits or reviews	 The results of any audits or reviews of sampling techniques and data. 	• The sampling and assay database has been reviewed by the company Qualified Person.

Section 2 Reporting of Exploration Results

(Criteria listed in the preceding section also apply to this section.)

Criteria		DRC Code explanation	Comme	entary
Mineral tenement and land tenure status	•	Type, reference name/number, location and ownership including agreements or material issues with third parties such as joint ventures, partnerships, overriding royalties, native title interests, historical sites, wilderness or national park and environmental settings. The security of the tenure held at the time of reporting along with any known impediments to obtaining a licence to operate in the area.	•	The The Woyla project tenement is held in the name of PT Woyla Aceh Minerals (PT WAM), which consists in 80% Woyla Aceh Ltd, 15% Quralon Pte Ltd, 2.5% PT Mutiara Mitramin, 2.5% PT Indo Noble Abadi. PT WAM holds a 6th Generation Contract of Work dated 17 March 1997. The Woyla Contract of Work was under a Mines Department approved state of suspension from exploration activities from 1999-2006 during the prolonged civil conflict in Aceh. An extended moratorium on exploration activities within Aceh has recently been lifted. The Contract of Work (177.K/30/DJB/2018) for the tenement was in voluntary suspension until FEG secured the necessary environmental and land use permits. FEG has recently been granted the environmental permit (PIPPIB) for 7688 ha of the protected forest area. This allows FEG to conduct exploration activities within the permit area under certain conditions.
Exploration done by other parties	•	Acknowledgment and appraisal of exploration by other parties.	•	Reconnaissance and detailed geological mapping were completed during 1996 – 1997 by Newcrest Mining and Barrick Gold. A helicopter-borne magnetic and radiometric survey was flown by World Geoscience in 1996. The companies collected stream, soil and rock samples of exposed veins and also completed petrology studies on selected samples.

Criteria	JC	ORC Code explanation	Cor	nmentary
Geology	•	Deposit type, geological setting and style of mineralisation.	•	The project area sits within the Neogene Gold Belt of Sumatra, characterised by Miocene-Neogene gold intrusion centred mineralisation. Along strike in a NW direction from the project area are the Miwah high-sulphidation gold deposit and Beutong- porphyry and skarn system and along strike to the SE lies the Abong (sediment hosted) and Meluak (high- sulphidation) gold deposits. Previous exploration has identified several low sulphidation, epithermal type Au-Ag bearing quartz/breccia systems hosted within and likely controlled by a series of fault structures related to the Sumatra Fault and emplacement of intrusions. As such, Au-Cu porphyry style, associated skarn and high- sulphidation Au may also be found within the Woyla project area. Downstream from the known veins systems are several alluvial-Au workings (Anu Renguet).
Drill hole Information	•	A summary of all information material to the understanding of the exploration results including a tabulation of the following information for all Material drill holes:		No previous drilling has been completed
		$\circ~$ easting and northing of the drill hole collar		
		 elevation or RL (Reduced Level – elevation above sea level in metres) of the drill hole collar 		
		$\circ~$ dip and azimuth of the hole		
		$\circ~$ down hole length and interception depth		
		 hole length. 		
	•	If the exclusion of this information is justified on the basis that the information is not Material and this exclusion does not detract from the understanding of the report, the Competent Person should clearly explain why this is the case.		
Data aggregation methods	•	In reporting Exploration Results, weighting averaging techniques, maximum and/or minimum grade truncations (eg cutting of high grades) and cut-off grades are usually Material and should be stated.		• All values are reported as assayed and no equivalent grades (eg. Au Eq) have been included.
	•	Where aggregate intercepts incorporate short lengths of high grade results and longer lengths of low grade results, the procedure used for such aggregation should be stated and some typical examples of such aggregations should be shown in detail.		
	•	The assumptions used for any reporting of metal equivalent values should be clearly stated.		

Criteria	JORC Code explanation	Commentary
Relationship between mineralisatio n widths and intercept lengths	 These relationships are particularly important in the reporting of Exploration Results. If the geometry of the mineralisation with respect to the drill hole angle is known, its nature should be reported. If it is not known and only the down hole lengths are reported, there should be a clear statement to this effect (eg 'down hole length, true width not known'). 	• The rock samples collected are considered a reflection of the nature of mineralization at the point of sampling. Aside from a visual estimation at the time of sampling no accurate determination of vein widths was made.
Diagrams	• Appropriate maps and sections (with scales) and tabulations of intercepts should be included for any significant discovery being reported These should include, but not be limited to a plan view of drill hole collar locations and appropriate sectional views.	 Pertinent maps and sections are included in the corporate release of sample results
Balanced reporting	• Where comprehensive reporting of all Exploration Results is not practicable, representative reporting of both low and high grades and/or widths should be practiced to avoid misleading reporting of Exploration Results.	 Reporting is fully representative of the data.
Other substantive exploration data	 Other exploration data, if meaningful and material, should be reported including (but not limited to): geological observations; geophysical survey results; geochemical survey results; bulk samples – size and method of treatment; metallurgical test results; bulk density, groundwater, geotechnical and rock characteristics; potential deleterious or contaminating substances. 	• All data is fully reported.
Further work	 The nature and scale of planned further work (eg tests for lateral extensions or depth extensions or large-scale step-out drilling). Diagrams clearly highlighting the areas of possible extensions, including the main geological interpretations and future drilling areas, provided this information is not commercially sensitive. 	 The company will incorporate the sample assay results into an 2022 exploration program to include detailed surface mapping, geophysics and initial drilling of priority vein targets to assess their resource potential.

Section 3 does not apply as the information regarding the mineral resource was prepared and first disclosed under the 2004 Edition of the 'Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves'. It has not been updated since to comply with the 2012 Edition of the 'Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves' on the basis that the Company is not aware of any new information or data that materially affects the information and, in the case of the resource estimate, all material assumptions and technical parameters underpinning the estimate continue to apply and have not materially changed. Section 4 does not apply as reserve estimates are not being disclosed at this time and Section 5 does not apply as this section relates to the reporting of diamonds and other gemstones.